

DOWNLIGHTS

LED-Canvas

ADO Lights by TTC Timmler Technology GmbH
 Christian-Schäfer-Str. 8 | 53881 Flammersheim
 T +49 2255 9212-00 | F +49 2255 9212-99
 info@ado-lights.com | www.ado-lights.com



BASE INFO, PICTURES AND TECHNICAL DRAWINGS



DIMENSIONS [L X W X H]	Luminaire housing: 110 x 110 x 77 mm
POWER CONSUMPTION	9/14 W
LUMINOUS FLUX	9 W: 676 lm 703 lm 880 lm 14 W: 1,055 lm 1,085 lm 1,392 lm
LIGHT BEAM ANGLE	24°/30°/38° tilt angle 30° rotatable 350°
SERVICE LIFE	LED 50,000 hours at 70% of mean luminous flux
COLOUR TEMPERATURE	White 2,700/3,000/4,000 Kelvin
CRI	CRI > 90 [CRI > 80]
CONTROL INTERFACE	With ballast, not dimmable
IP RATING	IP43

LUMINAIRE HOUSING	Aluminium white powder-coated or black powder-coated
CONVERTER	Overload protection Overtemperature protection Short-circuit protection
OPTIONS	»Dim to Warm«-LED mit 13 W, 1,000 lm, 2,000–3,000 Kelvin Dimmable ballast 1–10 V DALI Connection cable PoE-enabled
LIGHT CALCULATION	EULUM data see www.ado-lights.com

