

# DOWNLIGHTS

## LED-Gallery 10

ADO Lights by TTC Timmler Technology GmbH  
 Christian-Schäfer-Str. 8 | 53881 Flammersheim  
 T +49 2255 9212-00 | F +49 2255 9212-99  
 info@ado-lights.com | www.ado-lights.com



### BASE INFO, PICTURES AND TECHNICAL DRAWINGS



<b>DIMENSIONS [L X W X H]</b>	Luminaire housing: 284 x 48 x 49 mm Cut-out: 276 x 40 mm
<b>POWER CONSUMPTION</b>	15 W   10 reflectors
<b>LUMINOUS FLUX</b>	1,100 lm   1,150 lm   1,250 lm
<b>LIGHT BEAM ANGLE</b>	15°/30°/45°   rigid
<b>SERVICE LIFE</b>	LED 50,000 hours at 70% of mean luminous flux
<b>COLOUR TEMPERATURE</b>	White   2,700/3,000/4,000 Kelvin
<b>CRI</b>	CRI > 90
<b>CONTROL INTERFACE</b>	With ballast, not dimmable
<b>IP RATING</b>	IP20

<b>LUMINAIRE HOUSING</b>	Aluminium powder-coated white, black or grey
<b>CONVERTER</b>	Overload protection Overtemperature protection Short-circuit protection
<b>OPTIONAL</b>	Dimmable ballast 1–10 V DALI Connection cable With 6 mm polished glass covering IP54 PoE-enabled
<b>LIGHT CALCULATION</b>	EULUM data see <a href="http://www.ado-lights.com">www.ado-lights.com</a>

