
LED-BEWELL

Surface Mounted Luminaire
Pendant Luminaire

LED-BEWELL

Surface mounted Luminaire

Pendant Luminaire

ADO 

PICTURES



LED-BEWELL

Surface mounted Luminaire

Pendant Luminaire



BASE INFORMATION AND
TECHNICAL DRAWINGS »CIRCULAR«



LED-Be Well – for body and soul


Emotions can be controlled – by light as well. Which is why light is used as a therapy for depressive moods. And as a result light plays an important role in companies' production facilities: where it is bright employees are more motivated, and there is a positive effect on sickness levels. Small wonder, then, that brightness plays a pivotal role in hospitals, rehabilitation clinics, and hotels. Thus, on a trial basis, several rooms in the intensive care unit at the Charité's Virchow Clinic in Berlin were fitted with controllable LED lighting. The aim was to increase brightness when needed in order to promote the natural daytime-night-time rhythm, because not dozing during the day means you can get to sleep better at night.

Better orientation, less noise, plus sufficient light, all this affects convalescence and indeed well-being in everyday life. Positive effects such as these are precisely why the LED luminaire "Be well" was designed. The innovative ADO Lights product stands for high power: With 10,000 lumen the luminaire boasts the equivalent output of a light shower. Blue, violet, be it for



patients or a hotel setting: The hue of the light can be adjusted, as desired. The user just switches over. By means of remote control or app. The benefits are obvious: "Be well" brings more light into your life. More color. And that is good – for body and soul.

Features

- For hotels, hospitals, rehab clinics, baths private residences
- To create well-being
- Usable as a light shower
- Optionally controllable with remote control or app
- Circular or rectangular as surface mounted or pendant luminaire



ILLUMINANCE | POWER 36 W
COLOUR TEMPERATURE 4,000 K NEUTRAL WHITE







LED-BEWELL

Surface mounted Luminaire

Pendant Luminaire

ADO 

PICTURES



LED-BEWELL

Surface mounted Luminaire

Pendant Luminaire





TECHNICAL SPECIFICATION »CIRCULAR/RECTANGULAR«
AND TECHNICAL DRAWING »RECTANGULAR«




DIMENSIONS [L X W X H]	CIRC.: ø 500 mm REC.: 400 x 400 mm
POWER CONSUMPTION	36 W
LUMINOUS FLUX	LED WHITE: Module efficiency 92 lm/W Nominal luminous flux 1,760 lm Illuminance > 10,000 lm
OPERATING VOLTAGE	Low voltage up to 48V DC
SERVICE LIFE	LED + EVG 50,000 hours at 70% of mean luminous flux
COLOUR TEMPERATURE	White 4,000 Kelvin RGB
CRI	CRI > 85
NORM/PERFORMANCE	UGR < 19
CONTROL INTERFACE	dimmable Colour selection via two keys (control lines necessary) or via app »bluedimm« (iOS/Android)

IP RATING	IP54/65
LUMINAIRE HOUSING	Aluminium black anodised or powder-coated according to RAL
MOUNTING	PENDANT LUMINAIRE: Stainless steel cable and translucent supply line SURFACE MOUNTED LUMINAIRE: Screw-locking ceiling substructure
CONVERTER	Overload protection overtemperature protection Short-circuit protection
OPTIONAL	Remote control Controllable via app
WEIGHT	6.3 kg



ILLUMINANCE | POWER 36 W
COLOUR TEMPERATURE 4,000 K NEUTRAL WHITE



TTC Timmler Technology GmbH
Christian-Schäfer-Straße 8
D-53881 Flammersheim [Cologne/Bonn]
T +49 2255 9212-00
F +49 2255 9212-99
E info@ado-lights.com
I www.ado-lights.com
www.led-luc.com



by TTC Timmler Technology

